# Shoulder Houlder II

#### Warnings and Instructions: Review carefully, proper application is required

**Warning:** This device will not prevent or eliminate risk of injury. Do Not Overtighten. If swelling, pain, skin irritation, or an unusual reaction occurs, discontinue use immediately and consult your medical professional. Care: Hand wash using mild soap. Rinse thoroughly. Air dry only. Do not tumble dry.



1. Place pillow against body and secure waist strap around waist.



4. Have practitioner adjust back straps before first time use.



7. Completed application. Remove brace using quick release buckles.

See the remove pillow step down application on back





2. Place affected elbow in corner of elbow pocket. Attach brace to pillow.



5. Make final adjustments to brace using front straps.



3. Fasten ends of shoulder strap to front corners of brace. Secure arm in brace with elbow strap



6. Secure thumb strap.



755 Regent Blvd. Suite 250, DFW Airport, TX 75261 National: 800-654-3241 International: 805-525-4244, fax 805-933-2348 US fax: 800-559-5975, hely-weber.com



Scan to view application video

## Shoulder Houlder II Remove Pillow

#### Warnings and Instructions: Review carefully, proper application is required

**Warning:** This device will not prevent or eliminate risk of injury. Do Not Overtighten. If swelling, pain, skin irritation, or an unusual reaction occurs, discontinue use immediately and consult your medical professional. Care: Hand wash using mild soap. Rinse thoroughly. Air dry only. Do not tumble dry.

### REMOVE PILLOW STEP DOWN APPLICATION



 Use quick release clips to remove brace from patient. Remove pillow from brace. Detach straps from pillow.



12. Place affected elbow in corner of elbow pocket, and clip in shoulder strap.



- 10. Re-attach long end of swath strap to brace at elbow as shown.
- The strap adjustment fasteners need to be facing out.



13. Bring swath strap around back, and clip into fastener near front of brace.



11. Re-attach short piece of swath strap to front of brace as shown.



6. Make final adjustments to strap lengths.



755 Regent Blvd. Suite 250, DFW Airport, TX 75261 National: 800-654-3241 International: 805-525-4244, fax 805-933-2348 US fax: 800-559-5975, hely-weber.com